Sureline®

Air & Multipurpose General Purpose **Heavy Duty** Push-on

Chemical Transfer

Cleaning Equipment

Food Dry Transfer Liquid Transfer Washdown

Marine

Material Handling Abrasives **Bulk Transfer** Cement & Concrete

Mining

Petroleum Aircraft Fueling Dispensing Dock Rig Supply Transfer Discharge Transfer S&D

Specialty

Steam

Vacuum

Water Discharge Suction & Discharge Washdown Garden

Welding

Coupling Systems

Equipment

Appendix



Product Specifications

Application

Sureline® is for a wide range of industrial, construction, and agricultural water discharge applications in which a generalservice water hose is needed.

Construction

> Tube

EPDM synthetic rubber, ARPM Class C (Limited Oil Resistance)

> Cover

Red or black EPDM synthetic rubber

> Reinforcement Spiral synthetic yarn

Temperature Range

-40°F to 190°F (-40°C to 88°C)

Packaging

3/16"-3/4" - 500' reels, maximum 3 pieces, 50' increments 1" - 450' reels, maximum 3 pieces, 50' increments

1¼" - 400' reels, maximum 3 pieces, 50' increments

1½" - 300' reels, maximum 3 pieces, 50' increments

Branding (Spiral)

Example: 1/2" Sureline® Continental ContiTech 150 psi WP

Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Order Codes 569-048 (red) 569-049 (black)

Sureline®

SAP#		ID		Nom. OD		Max. WP		Weight	
Red	Black	in.	mm	in.	mm	psi	МРа	lb./ft.	kg/m
20026443	20026458	1/4	6.4	0.48	12.2	150	1.03	0.08	0.12
20026444	20026459	3/8	9.5	0.66	16.8	150	1.03	0.13	0.19
20026447	20026465	1/2	12.7	0.78	19.8	150	1.03	0.17	0.25
20026448	20026474	5/8	15.9	0.93	23.6	150	1.03	0.26	0.39
20026451	20026485	3/4	19.1	1.08	27.4	150	1.03	0.33	0.49
20026454	20026501	1	25.4	1.39	35.3	150	1.03	0.52	0.77
20026455	20026508	1-1/4	31.8	1.63	41.4	150	1.03	0.57	0.85
20026456	20026512	1-1/2	38.1	1.88	47.8	150	1.03	0.68	1.01

Hose design ratio (burst pressure) 4:1.