

## FLOW CENTERS: EA SERIES

### 2 CIRCUIT FLOW CENTERS

DESIGNED FOR DUAL UNITS - PUMPS ON EACH CIRCUIT FOR ONE COMMON LOOP FIELD.

#### SIMPLE INSTALLATION

The [EA Flow Center](#) is shipped to be assembled in the field. Installation is still simple. The system should be mounted on the floor. Wall bracket included. After mounting the pumps, simply connect a return line from the earth loop to the EA Flow Center. Then connect a supply line from the EA to the heat pump unit. That's all there is to adding reliable pump protection to any closed-loop system.

#### Features & Benefits

- Same Functionality as the QT® - EA Series
- 2 Year Limited Warranty
- Field Assembly Required
- Externally Mounted Pumps
- Foam Insulated Stainless Canister
- Mount Against Wall Style Unit (Bracket Included)



Part Number	# of Pumps	Voltage	Amps Grundfos (3 Speed)	HP (ea.)	Inlet/Outlet Size
0-0EASS230KFC	0	-	-	-	1-1/4" MPT/1-1/4" FPT
1-1EASS230KFC-G	2	230	1.8	1/6	1-1/4" MPT/1-1/4" FPT
2-1EASS230KFC-G	3	230	2.7	1/6	1-1/4" MPT/1-1/4" FPT
2-2EA230SSKFC-G	4	230	3.6	1/6	1-1/4" MPT/1-1/4" FPT
1-1EASS230KFC-M	2	230	3.6	1/6	1-1/4" MPT/1-1/4" FPT
2-1EA230SSKFC-M	3	230	5.4	1/6	1-1/4" MPT/1-1/4" FPT
2-2EA230SSKFC-M	4	230	7.2	1/6	1-1/4" MPT/1-1/4" FPT

Standard: MPT on Inlet Connection. Union can be Special Ordered.

Model Number Letter G=3-2699-3 Speed

M=26-116F (1.8 Amps per Pump)

See Pump Curve Section in Back of Catalog for Pump Performance Data



ALL THE "PUMP" YOU NEED AND MORE

1-866-646-6724  
712-652-3424  
[www.bdmfginc.com](http://www.bdmfginc.com)