

**FLOW CENTERS: XT FLOW CENTER**

The XT is designed to work with 7-12 ton single coil dual stage heat pumps.

**Features & Benefits**

Same Functionality as the QT® & GT® Series

2 Year Limited Warranty

**Construction:**

The XT is a stainless steel canister with brass check valves below the pumps. The canister is placed in a metal box and insulated with foam. All sections are factory assembled. The pumps are Grundfos UPS 43-100F 3 Speed Pumps.

**Check Valves:**

The check valve is to help with proper flow and pump protection.

**Insulation:**

The canister is insulated by foam to help eliminate condensation and is encased by a box design.

**Field Assembly:**

The unit has 1 1/4" female port for any type of male connection. An easy disconnect fitting is recommended.

**Isolation Ball Valves:**

The unit has a pair of isolation ball valves, allowing for removal and service of individual heat pumps while maintaining operability of the rest of the systems. Also, makes removal of pumps for replacement simple.

**Air Separation Chamber:**

The chamber continually performs a purging function to eliminate air.

Part Number	# of Pumps	Voltage	Amps Grundfos 43-100	HP (ea.)	Inlet*/Outlet Size
2-230XTSS*	2	230	3.4	1/6	1 1/4" FPT

**Grundfos \*43-100F 3 Speed Pump  
XT's Overall Size 48 1/2" x 10 x 22 1/2"**

\*Dimensions are approximate



**See Pump Curve Section in Back of Catalog for Pump Performance Data**



ALL THE "PUMP" YOU NEED AND MORE

**1-866-646-6724**  
**712-652-3424**  
[www.bdmfginc.com](http://www.bdmfginc.com)