



62676 - Leak Sealer F4 Express 400ml

Leak Sealer F4 is a internal leak sealer developed for use throughout a central heating system to seal small, inaccessible leaks and weeps which may cause pressure loss and boiler breakdown. Once dispersed within the system, the product finds the area of oxygen ingress and forms a polymer to seal the pinhole. Effective within 1-24 hours after application, the unique sealing efficiency of this market-leading water treatment chemical has been proven to prevent blockages or restrictions within the boiler or vulnerable system components such as pumps and safety devices. A leak can be quickly and efficiently sealed, without the need for a complete system drain down. The Fernox Express range uses Barrier Pressure Pack technology and compressed air propellant to expel the product so the entire range is non-flammable. The propellant (compressed air) is not mixed with the active product so there is no risk of air ingress into the system which could accelerate future risk of corrosion.

- Seeks out and seals inaccessible, internal microscopic leaks fast
- Quick and convenient – doses in 30 seconds - no need to drain down the system
- Safe to use - does not cause blockages in pipework or vulnerable boiler components such as pumps, air vents and heat exchangers
- Non-toxic, environmentally friendly formulation, compressed air propellant and 100% recyclable can
- Saves time and money on draining down and repairing.
- Add via a radiator, filling loop or TF1 System Filter - all adapters supplied

Application

A single dose of Leak Sealer F4 Express treats a larger sized property with a heating system of 34 US Gallons of system water (16 radiators) and the equivalent of 2690 sq ft of underfloor heating and can be dispensed directly into a radiator air vent, system filling loop, or via a TF1 Filter using the appropriate adapter supplied with the product. Fernox Express takes less then 30 seconds to dose the system without the need to drain down the system, saving time on-site. If dosing via a TF1 Filter, the filter should be emptied of any collected contaminants prior to treating with the product. In single feed indirect cylinder, e.g. 'Primatic' or similar, potable water chemicals must be used.

Packaging, Handling & Safety

Fernox Leak Sealer F4 Express is supplied in 13 fl oz aerosol cans with a universal applicator set.

Fernox Leak Sealer F4 Express is classified as non-hazardous, but as with all chemicals, keep out of reach of children. Do not mix with other chemicals. Do not take internally. In case of contact with eyes or skin, rinse immediately with plenty of water.

Specification

Colour: White
Form: Viscous liquid
Odour: Faint
pH: 5.0 - 7.0
SG: 1.0 @ 20°C

Volumetrics & Barcodes

Barcode EAN	5014551626768	OCU Barcode	05014551003378
Single Unit Weight (kg)	0.53	Outer Carton Weight (kg)	5.56
Single Unit Height (mm)	218	Outer Carton Height (mm)	241
Single Unit Width (mm)	66	Outer Carton Width (mm)	178
Single Unit Depth (mm)	95	Outer Carton Depth (mm)	339

Safety Data Sheet (US-EN-US)

[https://files.plytix.com/api/v1.1/file/public_files/pim/assets/45/7d/ae/5f/5fae7d45c573435950d65e1e/texts/04/0c/a8/69/69a80c04787fee2350ad9ebb/62676_Fernox SDS GHS Americas_English \(US\).pdf](https://files.plytix.com/api/v1.1/file/public_files/pim/assets/45/7d/ae/5f/5fae7d45c573435950d65e1e/texts/04/0c/a8/69/69a80c04787fee2350ad9ebb/62676_Fernox SDS GHS Americas_English (US).pdf)

Last Modified2026-05-20T14:29:27.292000