

Effective April, 2016 Supercedes January, 2014 1830 Centennial Ave. Hastings, NE 68901 Ph: 402-462-2227 Fax: 402-462-5529 Toll Free: 866-851-2227 centennialplastics.com



CenFuse

HDPE 4710 — ASTM D3035

Flexible polyethylene pipe

Produced from only the finest virgin material

- Backed by a **50-YEAR WARRANTY**
- All diameters are IPS, OD controlled and compatible with heat fusion.

| | | | | | | - | | | | |
|---------|----------|--------------|--------------------|-------------|---------------|-----------------|-----------------|------------|------------------------|---------------|
| ASTM | D3035 | | 3/4" | 1 " | 1-1/4" | 1-1/2" | 2" | 3" | 4" | 6" |
| 125 PSI | SDR 17 | 0.D. | 1.050" | 1.315" | 1.660" | 1.900" | 2.375" | 3.500" | 4.500" | 6.625" |
| | | I.D. | .926" | 1.161" | 1.464" | 1.676" | 2.095" | 3.088" | 3.970" | 5.971" |
| | | Wall | .062" | .077" | .098" | .112" | .140" | .206 " | .265" | .390" |
| | | Wt/Ft | .082# | .128# | .206# | .269# | .421# | .912# | 1.508# | 3.268# |
| | | Coil Lengths | | | | | | 500'/1000' | 500' | 40' |
| | | con zenguio | | - | | ONLY** | | 000,1000 | 000 | 10 |
| | | | 5/ 4 -2 | DIQU | | | | | | |
| 138 PSI | SDR 15.5 | 0.D. | N/A | N/A | 1.660" | 1.900" | 2.375" | 3.500" | 4.500" | 6.625" |
| | | I.D. | N/A | N/A | 1.446" | 1.654" | 2.069" | 3.048" | 3.920" | 5.771" |
| | | Wall | N/A | N/A | .107" | .123" | .153" | .226" | .290" | .427" |
| | | Wt/Ft | N/A | N/A | .223# | .294# | .457# | .994# | 1.641# | 3.5557# |
| | | Coil Lengths | 100-500 ft | | 100-500 ft | 100-500 ft | 100-500 ft | 40-500 ft | 40 ft | 40/20**ft |
| 160 PSI | SDR 13.5 | , | | | | | | | | |
| 100101 | SER IO.O | 0.D. | 1.050" | 1.315" | 1.660" | 1.900" | 2.375" | 3.500" | 4.500" | 6.625" |
| | | I.D. | .894" | 1.121 " | 1.414" | 1.618" | 2.023" | 2.982" | 3.834" | 5.643" |
| | | Wall | .078" | .097 " | .123" | .141" | .176" | .259" | .333" | .491" |
| | | Wt/Ft | .102# | .159# | .254# | .333# | .520# | 1.128# | 1.865# | 4.048# |
| | | Coil Lengths | Multiple Coi | Lengths and | Straight Leng | ths Available (| Jpon Request | 500'/1000' | 500' | 40' |
| 200 PSI | SDR 11 | O.D. | 1.050" | 1.315" | 1.660" | 1.900" | 2.375" | 3.500" | 4.500" | 6.625" |
| | | I.D. | .860" | 1.077" | 1.358" | 1.554" | 2.373 1.943" | 2.864" | 4.500 3.682" | 5.421 " |
| | | Wall | .095" | .120" | .151" | .173" | .216" | .318" | .409" | .602" |
| | | Wt/Ft | .122# | .120 | .306# | .402# | .627# | 1.36# | .409 2.249# | 4.873# |
| | | Coil Lengths | | | | | | 500'/1000' | 2.24 <i>7#</i> 500' | 4.873# 40' |
| | | con Lengths | - manpie con | Lengths and | Straight Leng | | opon Request | 50071000 | 500 | -10 |
| 250 PSI | SDR 9 | O.D. | 1.050" | 1.315" | 1.660" | 1.900" | 2.375" | 3.500" | 4.500" | N/A |
| | 1 | J.D. | .818" | 1.023" | 1.292" | 1.478" | 1.847" | 2.722" | 4.500 3.500" | N/A |
| | | Wall | .117" | .146" | .184" | .211" | .264" | .389" | .500" | N/A N/A |
| | | Wt/Ft | .146# | .229# | .365# | .479# | .749# | 1.626# | 2.688# | N/A |
| | | Coil Lengths | | | | | | 500'/1000' | 2.000# 500' | 40' |
| | | con Lengtils | indutiple Col | | Straight Leng | | opon nequest | 30071000 | 500 | 40 |

**Straight Lengths

Note: Other coil sizes and/or straight lengths are available upon request.

Note: CenFuse HDPE is suitable for connections by heat fusion or compression fittings of the same SDR

CenFuse meets AWWA C901 requirements in 3/4" - 3", SDR 9, 11 and 13.5

CenFuse meets AWWA C906 requirements in 4" - 6" all SDRs

Centennial Plastics, Inc. is an ISO 9001 Certified Company



CenFuse is tested and certified to NSF/ANSI Standard 14

All applicable CenFuse SDR's bear the NSF/ANSI 358-1 Certification Mark.

Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.